

## Declaration of Performance

No. DOP\_LE7S02\_12209

**1. Identification code of product type**

**Mortise lock series LE7S15xx and LE7S25xx**

**2. Name and address of the manufacturer**

Salto Systems S.L. (c/Arkotz, 9 - 20180 Oiartzun – Spain - CIF B20708517)

**3. Intended use of the construction product**

Mortise lock for fire doors

**4. System of assessment and verification of constancy of performance:** System 1

5. Notified body 1121 Exova (Ltd) performed initial tests, initial manufacturing plant inspection and surveillance, assessment and continuous approval of factory production center, under System 1 and issued the conformity certificate 1121-CPR-AG5163

**6. Declared performance**

Essential characteristics*	Performance		Harmonised technical specification
*Category of use	3	High frequency of use and misuse	EN 12209: 2003 +/AC : 2005
*Durability and load on latch bolt	M	200.000 cycles and y 25N on latch	
*Door mass and closing force	8	≤200 kg F closing ≤15N	
*Suitability for use on fire/smoke doors	1	Suitable for use on fire/smoke resisting doors	
Safety	0	No safety requirement	
Corrosion resistance and temperature	F	High corrosion resistance (96h)	
Security and drill resistance	2	Low security and without drilling resistance	
Field of door application	B	Mortise lock for hinged door	
Type of key operation and locking	A	Lock with cylinder. Manual blocking	
Type of spindle operation	2	Lever without spring	
Key identification	0	No requirements	

**7. The performance of the product identified in point 1, is in conformity with the declared performance in point 6.**

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2.



Oiartzun, 2017/08/30

Juan Imedio  
R&D Director